

SLK Superlift with counterweights



Technical data

| Technical data | SLK / 10 | SLK / 15 | SLK / 20 | SLK / 25 |
|----------------------------------|----------|----------|----------|----------|
| Lifting heights: | 3,50 m | 5,00 m | 6,50 m | 7,90 m |
| Transport position - height: | 1,98 m | 1,98 m | 1,98 m | 1,98 m |
| - length: | 0,90 m | 0,90 m | 0,96 m | 1,02 m |
| - width: | 0,80 m | 0,80 m | 0,80 m | 0,80 m |
| Working position - height: | 1,98 m | 1,98 m | 1,98 m | 1,98 m |
| - length: | 1,50 m | 1,80 m | 2,22 m | 2,22 m |
| - width: | 0,80 m* | 0,80 m* | 0,80 m* | 0,80 m* |
| Ground clearance min.: | 0,11 m | 0,11 m | 0,11 m | 0,11 m |
| Payload max. **: | 450 kg | 360 kg | 360 kg | 295 kg |
| Own weight: | 256 kg | 284 kg | 316 kg | 334 kg |
| Weight without attachment parts: | 122 kg | 150 kg | 182 kg | 200 kg |

* max. 2,22 m with lateral outriggers

** load center 36 cm